

MATERIAL SAFETY DATA SHEET

Control of Substances Hazardous to Health 2002 (COSHH) & International Standard ISO 11014-1

Section 1 Product and Company Identification

Kemmetech Lead Vinyl X-ray Scanner Protective Sheet - Available in a range of lead equivalent values. Solid, flexible sheet black in colour.

Kemmetech Limited, Unit 4 Arnold Business Park, Branbridges Road, East Peckham, Kent TN12 5LG. Tel: +44 (0)1622 872724; Fax: +44 (0)1622 871993

Section 2 Composition/Information on Ingredients

Composed of metallic lead, encapsulated in a vinyl resin and plasticiser matrix.

Section 3 Hazards Identification

Metallic lead, which is encapsulated in vinyl resin. Only hazardous if ingested. Lead has not been found to be a human carcinogen.

Section 4 First Aid Measures & Medical Information

SKIN: Lead has been reported to be only a mild skin irritant and absorption of inorganic lead through the skin is generally of no significance. Wash with soap and water.

EYES: Studies have shown that eye contact with lead causes only mild irritation and minimal inflammatory reactions. Flush well with running water to remove particulate. If irritation persists, get medical attention.

INHILATION: Remove from exposure, get medical attention.

INGESTION: Give water, induce vomiting and get medical attention.

Signs and Symptoms of Exposure: Systematic lead poisoning has symptoms of metallic taste, insomnia, weakness, constipation, abdominal pains and gastrointestinal disorder.

Medical Conditions Generally Aggravated by Exposure: Diseases of blood and blood forming organs, kidneys, nervous and possibly, reproductive systems.

Section 5 Fire-fighting Measures

Flammability: Self-extinguishing

Extinguishing: Carbon dioxide, dry chemicals or foam

Special Fire-fighting Measures: Use chemical mask

Section 6 Accidental Release Measures

Not applicable

Section 7 Handling & Storage

Cut edge of material is the main source of lead exposure. Wash hands after handling. Do not permit eating, drinking, smoking, or use of cosmetics while handling the material. Practice good personal hygiene. Wash hands and face thoroughly before eating or drinking.

Store in a clean, dry warehouse. Rolls should not be dropped and should be layed flat where possible. Do not expose material to excessive heat, above 50C and/or humidity levels exceeding 80%.

Section 8 Exposure Controls/Personal Protection

Latex (or equivalent) Gloves.

Section 9 Physical & Chemical Properties

Fully flexible sheeting supplied in various widths and roll lengths.

Section 10 Stability & Reactivity

Inherently stable, soluble in certain solvents

Section 11 Toxicological Properties

The toxicological effects of lead are the same whether it enters the body through breathing or swallowing. Lead can affect most organs and systems in the body. The main target for lead toxicity is the nervous system. Long-term exposure of adults can result in decreased performance in some tests that measure functions of the nervous system. It may also cause weakness in fingers, wrists, or ankles. Lead exposure also causes small increases in blood pressure, particularly in middle-aged and older people and can cause anemia. Exposure to high lead levels can damage the brain and kidneys, cause miscarriage and can damage the organs responsible for sperm production.

Section 12 Ecological Information

Lead is non degradable and will persist in the environment. It is insoluble in water and not attacked by most inorganic acids and bases.

Section 13 Disposal Considerations

Waste Disposal: Classified in Europe as non hazardous under EWC code 12 01 99. Should be disposed of in registered landfill sites in accordance with Local Authority regulations.

Section 14 Transport Information

Not classed as dangerous for transport by Carriage of dangerous goods by road and rail regulations 1994

Section 15 Regulatory Information

Classification: Not Classified

Section 16 Other Information

None

Section 17 Revision Dates

Date of Issue: December 2012
Revised date:
Replacing: All previous Material Safety Data Sheets

The information and recommendations on this sheet relate to the specific materials designated and may not be valid for material used in combination with any other materials or in any process. The information is given in good faith and is believed to be accurate at the time of preparation. Nothing hereon is to be construed as a guarantee express or implied, in all cases it is the responsibility of the user to determine the applicability of this information or the suitability of the products for their own particular purposes.